

Техническое описание продукта DULUX F 3600 W/830 106 V 2G10

OSRAM DULUX F | Плоские компактные люминесцентные лампы 4-штырьковым цоколем для ПРА/ЭПРА



Техническое описание продукта

Technical data

Электрические параметры

ZLDV_Nominal current [AGGR]	0.44 A A
-----------------------------	----------

Фотометрические данные

ZLDV_Light color (designation) [AGGR]	LUMILUX Warm White
ZLDV_Rated LLMF at 4,000 h [AGGR]	0.86
ZLDV_Rated LLMF at 6,000 h [AGGR]	0.83
ZLDV_Rated LLMF at 8,000 h [AGGR]	0.81
ZLDV_Rated LLMF at 12,000 h [AGGR]	0.77
ZLDV_Luminous flux [AGGR]	2800 lm
Индекс цветопередачи Ra	80...89

Размеры и вес

ZLDV_Overall length [AGGR]	221.00 mm
ZLDV_Tube diameter [AGGR]	17,5 mm
ZLDV_Length with base excl. base pins/connection [AGGR]	215,0 mm
ZLDV_Product weight [AGGR]	99.87 g

Температуры и условия управления

ZLDV_Ambient temperature range [AGGR]	-5...+40 °C
---------------------------------------	-------------

Срок службы

ZLDV_Service life [AGGR]	9000 h
Номинальный срок службы	10000 h

Дополнительные данные

Техническое описание продукта

ZLDV_Mercury content [AGGR]	2.5 mg
Утилизация по WEEE	Да

Сертификаты и Стандарты

ZLDV_Energy efficiency class [AGGR]	G
ZLDV_Energy consumption [AGGR]	38.00 kWh/1000h

Классификация

ZLDV_ILCOS [AGGR]	FSD-36/830-E-2G10-90/217
-------------------	--------------------------

Environmental information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (RECh)	
Date of Declaration	18-04-2022
Primary Article Identifier	4050300299051
Declaration No. in SCIP database	In work

Оборудование/аксессуары

– Подходит для использования с электронным и обычным ПРА

Ecodesign regulation information:

Separate control gear and light sources must be disposed of at certified disposal companies in accordance with Directive 2012/19/EU (WEEE) in the EU and with Waste Electrical and Electronic Equipment (WEEE) Regulations 2013 in the UK. For this purpose, collection points for recycling centres and take-back systems (CRSO) are available from retailers or private disposal companies, which accept separate control gear and light sources free of charge. In this way, raw materials are conserved and materials are recycled.

Данные для заказа

Product code	Описание продукта	Упаковка (цена/шт.)	Размеры (длина x ширина x высота)	Объем	Вес брутто
4050300299051	DULUX F 3600 W/830 106 V 2G10	Shipping carton box 10 шт. Folding carton box	290 mm x 100 mm x 245 mm	7.11 дм³	1562.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Ссылки

Более подробную информацию по электронному ПРА QUICKTRONIC см. на странице

Техническое описание продукта

► www.osram.com/QUICKTRONIC

Примечание

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

OSRAM is distribution partner
of LEDVANCE of LAMPS

OSRAM

OSRAM GmbH
Marcel-Breuer-Strasse 6
80807 Munich, Germany