

Техническое описание продукта

L 30 W/840

LUMILUX T8 | Трубчатые люминесцентные лампы трубчатой формы диаметром 26мм с цоколем **G13**



Техническое описание продукта

Technical data


Электрические параметры

ZLDV_Nominal current [AGGR]	0.37 A A
-----------------------------	----------

Фотометрические данные

ZLDV_Light color (designation) [AGGR]	LUMILUX Cool White
ZLDV_Rated LLMF at 2,000 h [AGGR]	0.96
ZLDV_Rated LLMF at 4,000 h [AGGR]	0.94
ZLDV_Rated LLMF at 6,000 h [AGGR]	0.93
ZLDV_Rated LLMF at 8,000 h [AGGR]	0.91
ZLDV_Rated LLMF at 12,000 h [AGGR]	0.91
ZLDV_Rated LLMF at 16,000 h [AGGR]	0.9
ZLDV_Rated LLMF at 20,000 h [AGGR]	0.96
ZLDV_Luminous flux [AGGR]	2400 lm

Размеры и вес



ZLDV_Tube diameter [AGGR]	26 mm
ZLDV_Length with base excl. base pins/connection [AGGR]	895,00 mm
ZLDV_Product weight [AGGR]	120.00 g
ZLDV_Overall length [AGGR]	908.80 mm

Срок службы

ZLDV_Service life [AGGR]	16000 h
--------------------------	---------

Дополнительные данные

ZLDV_Mercury content [AGGR]	3.0 mg
Утилизация по WEEE	Да

Техническое описание продукта

Сертификаты и Стандарты

ZLDV_Energy efficiency class [AGGR]	G
ZLDV_Energy consumption [AGGR]	32.00 kWh/1000h

Environmental information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
Date of Declaration	19-01-2022
Primary Article Identifier	4050300518039
Declaration No. in SCIP database	In work

Распределение силы света

FL_840

Системная гарантия

Расширенная системная гарантия OSRAM в сочетании с ЭПРА OSRAM

DUO CIRCUIT

Ecodesign regulation information:

Separate control gear and light sources must be disposed of at certified disposal companies in accordance with Directive 2012/19/EU (WEEE) in the EU and with Waste Electrical and Electronic Equipment (WEEE) Regulations 2013 in the UK. For this purpose, collection points for recycling centres and take-back systems (CRSO) are available from retailers or private disposal companies, which accept separate control gear and light sources free of charge. In this way, raw materials are conserved and materials are recycled.

Данные для заказа

Product code	Описание продукта	Упаковка (цена/шт.)	Размеры (длина x ширина x высота)	Объем	Вес брутто
4050300518039	L 30 W/840	Shipping carton box 25 шт. Sleeves	142 mm x 145 mm x 937 mm	19.29 дм³	3910.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Ссылки

Более подробную информацию по системной гарантии и положениям и условиям гарантийного обслуживания см. на странице <https://www.inventronics-light.com/multilevel-guarantees>

▶ www.inventronics-light.com/multilevel-guarantees

Более подробную информацию по электронному ПРА QUICKTRONIC см. на странице

▶ www.osram.com/QUICKTRONIC

Примечание

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

OSRAM is distribution partner
of LEDVANCE of LAMPS

OSRAM

OSRAM GmbH
Marcel-Breuer-Strasse 6
80807 Munich, Germany

L 30 W/840

LUMILUX T8 | Трубчатые люминесцентные лампы трубчатой формы диаметром 26мм с цоколем G13

Название продукта	Название продукта ЭПРА	EAN-код	Номиналь ный ток	Потери мощности	Световой поток при 25 °C	Число горелок
L 30 W/840	QT-FIT 5/8 1x18-39	4008321873927	0.15 A	33.00 Вт	2350 лм	1
	QT-FIT 5/8 2x18-39	4008321873903	0.27 A	63.00 Вт	2350 лм	2
	QTP-OPTIMAL 1x18-40	4008321873743	0.15 A	36.00 Вт		1
	QTP-OPTIMAL 2x18-40	4008321873767	0.28 A	63.00 Вт		2

Название продукта	Название продукта ЭПРА	EAN-код	Световой поток при 35 °C
L 30 W/840	QT-FIT 5/8 1x18-39	4008321873927	
	QT-FIT 5/8 2x18-39	4008321873903	
	QTP-OPTIMAL 1x18-40	4008321873743	2850 лм
	QTP-OPTIMAL 2x18-40	4008321873767	2850 лм