

Техническое описание продукта

HQI-T 250 W/D PRO

POWERSTAR HQI-T | Металлогалогенные лампы с кварцевой горелкой для закрытых светильников



Техническое описание продукта

Technical data

Электрические параметры

ZLDV_PFC capacitor at 50 Hz [AGGR]	32 µF
ZLDV_Ignition voltage [AGGR]	4.0/5.0 kVp
ZLDV_Nominal current [AGGR]	3 A A

Фотометрические данные

ZLDV_Rated LLMF at 2,000 h [AGGR]	0.95
ZLDV_Rated LLMF at 4,000 h [AGGR]	0.92
ZLDV_Rated LLMF at 6,000 h [AGGR]	0.9
ZLDV_Rated LLMF at 8,000 h [AGGR]	0.87
ZLDV_Rated LLMF at 12,000 h [AGGR]	0.85
ZLDV_UV protection [AGGR]	Yes
ZLDV_Luminous flux [AGGR]	18000 lm

Размеры и вес

ZLDV_Light center length (LCL) [AGGR]	150 mm
ZLDV_Product weight [AGGR]	150.00 g
ZLDV_Overall length [AGGR]	226.00 mm

Температуры и условия управления

ZLDV_Maximum permitted base edge temperature [AGGR]	250 °C
---	--------

Срок службы

ZLDV_Lifespan B50 [AGGR]	16000 h
--------------------------	---------

Дополнительные данные

Техническое описание продукта

ZLDV_Design / version [AGGR]	Clear
ZLDV_Mercury content [AGGR]	21.0 mg
Утилизация по WEEE	Да

Возможности / мощности

ZLDV_Burning position [AGGR]	Any
ZLDV_Enclosed luminaire required [AGGR]	Yes

Сертификаты и Стандарты

ZLDV_Energy efficiency class [AGGR]	G
ZLDV_Energy consumption [AGGR]	260.00 kWh/1000h

Классификация

ZLDV_ILCOS [AGGR]	MT/UB-250/952-H/E/SL-E40-46/226
-------------------	---------------------------------

Environmental information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
Date of Declaration	13-05-2022
Primary Article Identifier	4008321677846
Candidate List Substance 1	No declarable substances contained
Declaration No. in SCIP database	No declarable substances contained

Распределение силы света

HQI_T_D_PRO

OPERATION OF HIGH INTENSITY DISCHARGE LAMPS
WITH SEMI-PARALLEL IGNITION UNIT

OPERATION OF HIGH INTENSITY DISCHARGE LAMPS
WITH A SUPERIMPOSED IGNITION UNIT

OPERATION OF HIGH INTENSITY DISCHARGE LAMPS
WITH PULSE IGNITION UNIT

Ecodesign regulation information:

Separate control gear and light sources must be disposed of at certified disposal companies in accordance with Directive 2012/19/EU (WEEE) in the EU and with Waste Electrical and Electronic Equipment (WEEE) Regulations 2013 in the UK. For this purpose, collection points for recycling centres and take-back systems (CRSO) are available from retailers or private disposal companies, which accept separate control gear and light sources free of charge. In this way, raw materials are conserved and materials are recycled.

Данные для заказа

Product code	Описание продукта	Упаковка (цена/шт.)	Размеры (длина x ширина x высота)	Объем	Вес брутто
4008321677846	HQI-T 250 W/D PRO	Shipping carton box 12 шт. Sleeves	216 mm x 166 mm x 272 mm	9.75 дм³	2366.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Примечание

В заказ могут быть внесены изменения без предварительного уведомления. Проверьте информацию на наличие ошибок. Убедитесь, что информация актуальна.

OSRAM is distribution partner
of LEDVANCE of LAMPS

OSRAM

OSRAM GmbH
Marcel-Breuer-Strasse 6
80807 Munich, Germany

HQI-T 250 W/D PRO

POWERSTAR HQI-T | Металлогалогенные лампы с кварцевой горелкой для закрытых светильников