

Данные о продуктовой линейке SubstiTUBE Value

Economic LED tubes for electromagnetic control gears (CCG)



- General illumination within ambient temperatures from -20...+45 °C Corridors, stairways, parking garages Industry Warehouses Cooling and storage rooms Warehouses Domestic applications Supermarkets and department stores

- No bending thanks to glass tube Energy savings of up to 68 % (compared to T8 fluorescent lamp on CCG) Quick, simple and safe replacement without rewiring Instant-on light, therefore ideally suitable in combination with sensor technology Very high resistance to switching loads Also suitable for operation at low temperatures



Данные о продуктовой линейке

Technical data							
Электрические параметры							
Описание продукта	ZLDV_Claimed equiv. conventional lamp power [AGGR]	ZLDV_Nominal current [AGGR]	ZLDV_Nominal voltage [AGGR]	ZLDV_Nominal wattage [AGGR]	ZLDV_Max. lamp no. on circuit break. 16 A (B) [AGGR]	ZLDV_Max. lamp no. on circuit break. 10 A (B) [AGGR]	ZLDV_Operating frequency [AGGR]
ST8V-EM 7.3 W/840 600 mm	18 W	0.035 A	220...240 V	7.30 W	320	200	50...60 Hz
7.3 W/865 600 mm	18 W	35 mA					50...60 Hz
16.4 W/840 1200 mm	36 W	75 mA					50...60 Hz
16.4 W/865 1200 mm	36 W	75 mA					50...60 Hz
ST8V-EM 20 W/840 1500 mm	58 W	0.095 A	220...240 V	20.00 W	117	73	50...60 Hz
2000 W/865 1500 mm	58 W	95 mA					50...60 Hz
Фотометрические данные							
Описание продукта	ZLDV_Rated wattage [AGGR]	ZLDV_Nominal luminous flux [AGGR]	ZLDV_Light color (designation) [AGGR]	ZLDV_Color temperature [AGGR]	ZLDV_Color rendering index Ra [AGGR]	ZLDV_Lumen main.fact.at end of nom.life time [AGGR]	ZLDV_Rated luminous flux [AGGR]
ST8V-EM 7.3 W/840 600 mm	7.30 W	800 lm	Cool White	4000 K	≥80	0.70	800 lm
7.3 W/865 600 mm			Cool Daylight				
16.4 W/840 1200 mm			Cool White				
16.4 W/865 1200 mm			Cool Daylight				
ST8V-EM 20 W/840 1500 mm	20.00 W	2200 lm	Cool White	4000 K	≥80	0.70	2200 lm
2000 W/865 1500 mm			Cool Daylight				
Светотехнические параметры							
				Размеры и вес			
Описание продукта	ZLDV_Standard deviation of color matching [AGGR]	ZLDV_Starting time [AGGR]	ZLDV_Beam angle [AGGR]	ZLDV_Product weight [AGGR]	ZLDV_Overall length [AGGR]	ZLDV_Outer bulb [AGGR]	ZLDV_Diameter [AGGR]
ST8V-EM 7.3 W/840 600 mm	≤6 sdc	< 0.5 s	190 °	100.00 g	603.0 mm	T8	
7.3 W/865 600 mm			190 °	100.00 g	603.00 mm		

Данные о продуктовой линейке

		Светотехнические параметры		Размеры и вес			
Описание продукта	ZLDV_Standard deviation of color matching [AGGR]	ZLDV_Starting time [AGGR]	ZLDV_Beam angle [AGGR]	ZLDV_Product weight [AGGR]	ZLDV_Overall length [AGGR]	ZLDV_Outer bulb [AGGR]	ZLDV_Diameter [AGGR]
16.4 W/840 1200 mm			190 °	190.00 g	1212.00 mm		
16.4 W/865 1200 mm			190 °	190.00 g	1212.00 mm		
ST8V-EM 20 W/840 1500 mm	≤6 sdcм	< 0.5 s	190 °	230.00 g	1513 mm	T8	26.7 mm
2000 W/865 1500 mm			190 °	230.00 g	1513.00 mm		

		Температуры и условия управления	Срок службы				Дополнительные данные
Описание продукта	ZLDV_Length [AGGR]	ZLDV_Ambient temperature range [AGGR]	ZLDV_Number of switching cycles [AGGR]	ZLDV_Lumen maintenance at end of service life [AGGR]	ZLDV_Rated lamp life time LEDr [AGGR]	ZLDV_Nominal lamp life time [AGGR]	Последующая модель EAN
ST8V-EM 7.3 W/840 600 mm		-20...+45 °C	200000	0.70	30000 h	30000 h	4058075454460, 4058075024632
7.3 W/865 600 mm		-20...+45 °C		0.7			4058075454484, 4058075024656
16.4 W/840 1200 mm		-20...+45 °C		0.7			4058075454521, 4058075024694
16.4 W/865 1200 mm		-20...+45 °C		0.7			4058075454545, 4058075024717
ST8V-EM 20 W/840 1500 mm	1513 mm	-20...+45 °C	200000	0.70	30000 h	30000 h	4058075454583, 4058075024755
2000 W/865 1500 mm		-20...+45 °C		0.7			4058075454606, 4058075024779

Данные о продуктовой линейке

				Возможности / мощности	Сертификаты и Стандарты		
Описание продукта	Последующая модель EAN	ZLDV_Base (standard designation) [AGGR]	ZLDV_Mercury-free [AGGR]	ZLDV_Dimmable [AGGR]	ZLDV_Type of protection [AGGR]	ZLDV_Energy consumption [AGGR]	ZLDV_Energy efficiency class [AGGR]
ST8V-EM 7.3 W/840 600 mm	4058075611634	G13	Yes	No	IP20	8 kWh/1000h	E
7.3 W/865 600 mm	4058075611658		Yes			8.00 kWh/1000h	E
16.4 W/840 1200 mm	4058075611696		Yes			17.00 kWh/1000h	E
16.4 W/865 1200 mm	4058075611719		Yes			17.00 kWh/1000h	E
ST8V-EM 20 W/840 1500 mm	4058075611757	G13	Yes	No	IP20	20 kWh/1000h	E
2000 W/865 1500 mm	4058075611771		Yes			20.00 kWh/1000h	E

		Классификация	Environmental information Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)		
Описание продукта	ZLDV_Order reference [AGGR]	Date of Declaration	Primary Article Identifier	Declaration No. in SCIP database	
ST8V-EM 7.3 W/840 600 mm	ST8V-0.6M 7,3W/	18-04-2022	4058075454460 4058075611634	In work	
7.3 W/865 600 mm		13-07-2022	4058075454484 4058075611658	In work	
16.4 W/840 1200 mm		18-04-2022	4058075454521 4058075611696	In work	
16.4 W/865 1200 mm		18-04-2022	4058075454545 4058075611719	In work	
ST8V-EM 20 W/840 1500 mm	ST8V-1.5M 20W/8	18-04-2022	4058075454583 4058075611757	In work	
2000 W/865 1500 mm		18-04-2022	4058075454606 4058075611771	In work	

Данные о продуктовой линейке



ST8V-EM 7.3 W/840 600 mm, 16.4 W/840 1200 mm, 16.4 W/865 1200 mm, ST8V-EM 20 W/840 1500 mm, 2000 W/865 1500 mm

7.3 W/865 600 mm

Оборудование/аксессуары

– Предназначено для работы с ЭМПРА с низкими потерями

Рекомендации по применению

Для получения дополнительной информации и изображения продукции, пожалуйста, ознакомьтесь с инструкцией.

Данные о продуктовой линейке

Ecodesign regulation information:

Separate control gear and light sources must be disposed of at certified disposal companies in accordance with Directive 2012/19/EU (WEEE) in the EU and with Waste Electrical and Electronic Equipment (WEEE) Regulations 2013 in the UK. For this purpose, collection points for recycling centres and take-back systems (CRSO) are available from retailers or private disposal companies, which accept separate control gear and light sources free of charge. In this way, raw materials are conserved and materials are recycled.

Данные для заказа

Product code	Описание продукта	Упаковка (цена/шт.)	Размеры (длина x ширина x высота)	Объем	Вес брутто
4058075611634	ST8V-EM 7.3 W/840 600 mm	Shipping carton box 10	690 mm x 210 mm x 115 mm	16.66 дм³	1649.00 g
4058075611658	7.3 W/865 600 mm	Shipping carton box 10	690 mm x 210 mm x 115 mm	16.66 дм³	1649.00 g
4058075611696	16.4 W/840 1200 mm	Shipping carton box 10	1290 mm x 210 mm x 105 mm	28.44 дм³	2796.00 g
4058075611719	16.4 W/865 1200 mm	Shipping carton box 10	1290 mm x 210 mm x 105 mm	28.44 дм³	2796.00 g
4058075611757	ST8V-EM 20 W/840 1500 mm	Shipping carton box 10	1590 mm x 210 mm x 115 mm	38.40 дм³	3477.00 g
4058075611771	2000 W/865 1500 mm	Shipping carton box 10	1590 mm x 210 mm x 115 mm	38.40 дм³	3477.00 g
4058075611771	2000 W/865 1500 mm	Shipping carton box 10	1590 mm x 170 mm x 95 mm	25.68 дм³	3386.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Примечание

В заказ могут быть внесены изменения без предварительного уведомления. Проверьте информацию на наличие ошибок. Убедитесь, что информация актуальна.

OSRAM is distribution partner
of LEDVANCE of LAMPS

OSRAM

OSRAM GmbH
Marcel-Breuer-Strasse 6
80807 Munich, Germany