

# Техническое описание продукта

## 16.4 W/840 1200 mm

**SubstiTUBE Value | Economic LED tubes for electromagnetic control gears (CCG)**



- General illumination within ambient temperatures from -20...+45 °C Corridors, stairways, parking garages Industry Warehouses Cooling and storage rooms Warehouses Domestic applications Supermarkets and department stores

- No bending thanks to glass tube Energy savings of up to 68 % (compared to T8 fluorescent lamp on CCG) Quick, simple and safe replacement without rewiring Instant-on light, therefore ideally suitable in combination with sensor technology Very high resistance to switching loads Also suitable for operation at low temperatures



Техническое описание продукта

Technical data

Электрические параметры

ZLDV_Operating frequency [AGGR]	50...60 Hz
ZLDV_Nominal current [AGGR]	75 mA
ZLDV_Claimed equiv. conventional lamp power [AGGR]	36 W

Фотометрические данные

ZLDV_Light color (designation) [AGGR]	Cool White
ZLDV_Luminous flux [AGGR]	1800 lm

Светотехнические параметры

ZLDV_Beam angle [AGGR]	190 °
------------------------	-------

Размеры и вес



ZLDV_Product weight [AGGR]	190.00 g
ZLDV_Overall length [AGGR]	1212.00 mm

Температуры и условия управления

ZLDV_Ambient temperature range [AGGR]	-20...+45 °C
---------------------------------------	--------------

Срок службы

ZLDV_Lumen maintenance at end of service life [AGGR]	0.7
--	-----

Дополнительные данные

Утилизация по WEEE	Да
Последующая модель EAN	4058075611696
ZLDV_Mercury content [AGGR]	0.0 mg
ZLDV_Mercury-free [AGGR]	Yes

Техническое описание продукта

Последующая модель EAN	4058075454521, 4058075024694
------------------------	------------------------------

Сертификаты и Стандарты

ZLDV_Energy efficiency class [AGGR]	E
ZLDV_Energy consumption [AGGR]	17.00 kWh/1000h

Environmental information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
Date of Declaration	18-04-2022
Primary Article Identifier	4058075454521   4058075611696
Declaration No. in SCIP database	In work

Оборудование/аксессуары

– Предназначено для работы с ЭМПРА с низкими потерями

Ecodesign regulation information:

Separate control gear and light sources must be disposed of at certified disposal companies in accordance with Directive 2012/19/EU (WEEE) in the EU and with Waste Electrical and Electronic Equipment (WEEE) Regulations 2013 in the UK. For this purpose, collection points for recycling centres and take-back systems (CRSO) are available from retailers or private disposal companies, which accept separate control gear and light sources free of charge. In this way, raw materials are conserved and materials are recycled.

Данные для заказа

Product code	Описание продукта	Упаковка (цена/шт.)	Размеры (длина x ширина x высота)	Объем	Вес брутто
4058075611696	16.4 W/840 1200 mm	Shipping carton box 10 шт. Sleeves	1290 mm x 210 mm x 105 mm	28.44 дм³	2796.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Примечание

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

OSRAM is distribution partner  
of LEDVANCE of LAMPS

**OSRAM**

OSRAM GmbH  
Marcel-Breuer-Strasse 6  
80807 Munich, Germany