

TF2000TW -G1-827.865-05

TEC FLEX Tunable White IP00 | Светодиодные модули для полупрофессионального применения



Характеристики продукта

- Гибкая делимая светодиодная лента
- Color consistency in 3 SDCM
- Up to 50,000 hrs lifetime @ tc max

Преимущества продукта

- Простой монтаж на различных гладких поверхностях с помощью клейкой ленты с обратной стороны

Области применения

- Освещение, задающее настроение



Техническое описание продукта

Technical data


Электрические параметры

Номинальное напряжение	24,0 В
Тип тока	Постоянный ток
Мощность	54,00 Вт
Диапазон входных напряжений тока	23...25 В
Accidental reverse input voltage protection up to	25 В

Фотометрические данные

Цветность светодиода	Dynamic White
Индекс цветопередачи Ra	80
Световая отдача	143,7 лм/Вт
Цветность света (обозначение)	Dynamic White
Световой поток на метр	1940 лм

Размеры и вес



Длина	5000,0 mm
Вес продукта	70,00 g
Сечения кабеля, сторона ввода	0,5 mm ²
Ширина	8,00 mm
Высота	1,50 mm

Температуры и условия управления

Диапазон температур в процессе работы	-25...80 °C
t хранения	-30...85 °C

Дополнительные данные

ID of contained light source [AGGR]	LS_SHZ_600420
-------------------------------------	---------------

Техническое описание продукта

Сертификаты и Стандарты

Energy efficiency class of the contained light source	E
---	---

Условия поставки

Код заказа	85395100000
------------	-------------

Environmental information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
Date of Declaration	07-07-2023
Primary Article Identifier	4062172154246
Candidate List Substance 1	Lead
CAS No. of substance 1	7439-92-1
Safe Use Instruction	The identification of the Candidate List substance is sufficient to allow safe use of the article.
Declaration No. in SCIP database	2a9b6214-6b50-4973-89be-689a4910f27a

Оборудование/аксессуары

– Упрощенное подключение с помощью дополнительной подходящей системы CONNECTsystem

Загрузка данных

Файл	
	User instruction TEC Flex Tunable White, TEC Flex RGB
	Product Datasheet TEC Flex Tunable White IP00 product datasheet, EN
	Brochures Light is strong - Discover the versatile and flexible lighting system OSRAM 24V TEC Flex (EN)
	Certificates TEC Flex TW CE 4228593 210820
	Certificates TF(P)2000TW ENEC 071020
	Eulumdat Eulumdat TF2000TW-LDT
	IES data Eulumdat TF2000TW-IES

Техническое описание продукта

Ecodesign regulation information:

- This product is considered to be a "containing product" in the sense of Regulations (EU) 2019/2020 and (EU) 2019/2015.
- Tolerances of the reported values, are according to LED Modules Performance standard IEC/EN 62717.
- In general, the replacement of the contained light sources without permanent damage to the product with the use of common available tools is possible in the final application when they can be dismantled from the installation environment and substituted for the necessary number of light sources restoring its full electrical/mechanical/thermal/optical functionality by means of a professional installer. In the contrary, and limited to the LINEARlight Flex Diffuse, LINEARlight Rigid Finesse, GINO LED Flex Diffuse and LUMINENT Milky product families, the contained light source is an integrated part of the containing product and its removal can only be done by causing a permanent damage to the containing product due to its tight mechanical, electrical, optical, thermal interaction and/or environmental protection with or from the containing product. Therefore, a replacement of the light source with the use of common available tools is not justified.
- Dismantling of light sources from containing products at end of life: Containing products with light sources which are scalable in length can be cut to the length of the contained light source and if applicable mechanically detached from protective and/or optical covers. Containing products shall be separated from building material and/or from other additional mounting accessories by means of a professional installer. Separate control gear and light sources must be disposed of at certified disposal companies in accordance with Directive 2012/19/EU (WEEE) in the EU and with Waste Electrical and Electronic Equipment (WEEE) Regulations 2013 in the UK. For this purpose, collection points for recycling centres and take-back systems (CRSO) are available from retailers or private disposal companies, which accept separate control gear and light sources free of charge. In this way, raw materials are conserved and materials are recycled.

Данные для заказа

Product code	Описание продукта	Упаковка (цена/шт.)	Размеры (длина x ширина x высота)	Объем	Вес брутто
4062172154246	TF2000TW -G1-827.865-05	Shipping carton box 10	225 mm x 240 mm x 120 mm	6.48 дм³	1354.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Дополнительные аксессуары

Описание продукта	Название аксессуара	Код аксессуара
TF2000TW -G1-827.865-05	CORNER-FLEX -4P-003 KIT 10PCS	▶ 4062172179638
TF2000TW -G1-827.865-05	CONN-FLEX -3P-050 KIT 10PCS	▶ 4062172179690
TF2000TW -G1-827.865-05	CONN-FLEX -3P-200 KIT 10PCS	▶ 4062172179720
TF2000TW -G1-827.865-05	LTS-SLIMTRACK -2000 KIT 5 PCS	▶ 4062172207300
TF2000TW -G1-827.865-05	FX-QMS-G1 -TU15H6-300	▶ 4052899448865
TF2000TW -G1-827.865-05	FX-QMS-G1 -TU15H6W3-300	▶ 4052899448889
TF2000TW -G1-827.865-05	FX-QMS-G1 -TU16H12W3-300	▶ 4052899448988
TF2000TW -G1-827.865-05	FX-QMS-G1 -TU16H12-300	▶ 4052899448964
TF2000TW -G1-827.865-05	FX -SC08-G2-CT4PJ	▶ 4052899464858
TF2000TW -G1-827.865-05	FX-QMS-G1 -TU16H12LS-300	▶ 4052899449046

Техническое описание продукта

Примечание

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.