

TFP2000TW -G1-827.865-05

TEC Flex Protect Tunable White | Светодиодные модули для полупрофессионального применения



Характеристики продукта

- Гибкая делимая светодиодная лента
- Color consistency in 3 SDCM
- Up to 50,000 hrs lifetime @ tc max

Преимущества продукта

- Простой монтаж на различных гладких поверхностях с помощью клейкой ленты с обратной стороны

Области применения


- Освещение, задающее настроение



Техническое описание продукта

Technical data

Размеры и вес



Вес продукта	305,00 g
Длина	5000,0 mm
Ширина	11,1 mm
Высота	4,10 mm

Дополнительные данные

ID of contained light source	LS_SHZ_600421
------------------------------	---------------






Сертификаты и Стандарты

Energy efficiency class of the contained light source	E
---	---

Условия поставки

Код заказа	940540399000
------------	--------------

Загрузка данных

Файл	
	User instruction TEC Flex Protect Tunable White, TEC Flex Protect RGB
	Product Datasheet TEC Flex Tunable White IP66 product datasheet (EN)
	Brochures Light is strong - Discover the versatile and flexible lighting system OSRAM 24V TEC Flex (EN)
	Certificates TEC Flex TW CE 4228593 210820
	Certificates TF(P)2000TW ENEC 071020

Техническое описание продукта



Eulumdat
Eulumdat TFP2000TW-LDT



IES data
Eulumdat TFP2000TW-IES

Ecodesign regulation information:

ul>This product is considered to be a "containing product" in the sense of Regulations (EU) 2019/2020 and (EU) 2019/2015. Tolerances of the reported values, are according to LED Modules Performance standard IEC/EN 62717.

In general, the replacement of the contained light sources without permanent damage to the product with the use of common available tools is possible in the final application when they can be dismantled from the installation environment and substituted for the necessary number of light sources restoring its full electrical/mechanical/thermal/optical functionality by means of a professional installer.

In the contrary, and limited to the LINEARlight Flex Diffuse, LINEARlight Rigid Finesse, GINO LED Flex Diffuse and LUMINENT Milky product families, the contained light source is an integrated part of the containing product and its removal can only be done by causing a permanent damage to the containing product due to its tight mechanical, electrical, optical, thermal interaction and/or environmental protection with or from the containing product. Therefore, a replacement of the light source with the use of common available tools is not justified.

Dismantling of light sources from containing products at end of life: Containing products with light sources which are scalable in length can be cut to the length of the contained light source and if applicable mechanically detached from protective and/or optical covers. Containing products shall be separated from building material and/or from other additional mounting accessories by means of a professional installer.

Separate control gear and light sources must be disposed of at certified disposal companies in accordance with Directive 2012/19/EU (WEEE) in the EU and with Waste Electrical and Electronic Equipment (WEEE) Regulations 2013 in the UK. For this purpose, collection points for recycling centres and take-back systems (CRSO) are available from retailers or private disposal companies, which accept separate control gear and light sources free of charge. In this way, raw materials are conserved and materials are recycled.

Данные для заказа

Product code	Описание продукта	Упаковка (цена/шт.)	Размеры (длина x ширина x высота)	Объем	Вес брутто
4062172154260	TFP2000TW -G1-827.865-05	Shipping carton box 10	280 mm x 305 mm x 180 mm	15.37 дм ³	4024.00 г

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Примечание

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.