

Техническое описание продукта

SLIM LINE R7s 600 W/827 R7s

LED SLIM LINE R7S | Slim LED lamps with retrofit base R7s



- General illumination within ambient temperatures from -20...+40 °C Outdoor applications only in suitable luminaires

- Particularly compact dimensions Lower thermal output (compared with the standard reference product) Long lifetime of up to 15,000 h Three year guarantee



Техническое описание продукта

Technical data

Электрические параметры

ZLDV_Rated wattage [AGGR]	6.00 W
ZLDV_Nominal wattage [AGGR]	6.00 W
ZLDV_Nominal voltage [AGGR]	220...240 V
ZLDV_Operating frequency [AGGR]	50/60 Hz
ZLDV_Max. lamp no. on circuit break. 10 A (B) [AGGR]	141
ZLDV_Max. lamp no. on circuit break. 16 A (B) [AGGR]	178
ZLDV_Nominal current [AGGR]	0.045 A
ZLDV_Claimed equiv. conventional lamp power [AGGR]	60 W


Фотометрические данные

ZLDV_Rated color temperature [AGGR]	2700 K
ZLDV_Color rendering index Ra [AGGR]	80
ZLDV_Light color (designation) [AGGR]	Warm White
ZLDV_Standard deviation of color matching [AGGR]	≤6 sdc _m
ZLDV_Rated luminous flux [AGGR]	806 lm
ZLDV_Nominal luminous flux [AGGR]	806 lm
ZLDV_Color temperature [AGGR]	2700 K
ZLDV_Luminous flux [AGGR]	806 lm
ZLDV_Lumen main.fact.at end of nom.life time [AGGR]	0.70

Светотехнические параметры

ZLDV_Beam angle [AGGR]	300 °
ZLDV_Starting time [AGGR]	< 0.5 s

Размеры и вес



ZLDV_Overall length [AGGR]	78.0 mm
----------------------------	---------

Техническое описание продукта

ZLDV_Product weight [AGGR]	18.00 g
ZLDV_Length [AGGR]	78.0 mm
ZLDV_Outer bulb [AGGR]	T20
ZLDV_Diameter [AGGR]	20.0 mm

Температуры и условия управления

ZLDV_Ambient temperature range [AGGR]	-20...+40 °C
---------------------------------------	--------------

Срок службы

ZLDV_Nominal lamp life time [AGGR]	15000 h
ZLDV_Rated lamp life time LEDr [AGGR]	15000 h
ZLDV_Number of switching cycles [AGGR]	100000
ZLDV_Lumen maintenance at end of service life [AGGR]	0.70

Дополнительные данные

ZLDV_Base (standard designation) [AGGR]	R7s
ZLDV_Mercury-free [AGGR]	Yes
Утилизация по WEEE	Да
Последующая модель EAN	4058075432710
ZLDV_Mercury content [AGGR]	0.0 mg
Последующая модель EAN	4058075432710

Возможности / мощности

ZLDV_Dimmable [AGGR]	No
----------------------	----

Сертификаты и Стандарты

ZLDV_Energy efficiency class [AGGR]	E
ZLDV_Energy consumption [AGGR]	6 kWh/1000h
ZLDV_Type of protection [AGGR]	IP20

Классификация

ZLDV_Order reference [AGGR]	LESLIM7860 6W/8
-----------------------------	-----------------

Environmental information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
Date of Declaration	18-04-2022
Primary Article Identifier	4058075432710
Declaration No. in SCIP database	In work

Техническое описание продукта

Ecodesign regulation information:

Separate control gear and light sources must be disposed of at certified disposal companies in accordance with Directive 2012/19/EU (WEEE) in the EU and with Waste Electrical and Electronic Equipment (WEEE) Regulations 2013 in the UK. For this purpose, collection points for recycling centres and take-back systems (CRSO) are available from retailers or private disposal companies, which accept separate control gear and light sources free of charge. In this way, raw materials are conserved and materials are recycled.

Данные для заказа

Product code	Описание продукта	Упаковка (цена/шт.)	Размеры (длина x ширина x высота)	Объем	Вес брутто
4058075432710	SLIM LINE R7s 600 W/827 R7s	Shipping carton box 6 шт. Folding carton box	111 mm x 83 mm x 106 mm	0.98 дм³	354.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Примечание

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

OSRAM is distribution partner
of LEDVANCE of LAMPS

OSRAM

OSRAM GmbH
Marcel-Breuer-Strasse 6
80807 Munich, Germany