

LFP3400TW-G5 -825.940-03 L1

LINEARlight FLEX Tunable White Protect | LED modules for professional and industrial applications



Характеристики продукта

- 24 V LED strips flexible and cuttable
- Luminous flux: up to 3,400 lm/m
- Up to 60,000 h L90/B10 with SDT technology, tested acc. to IEC 62717 on real LED strips
- Adjustable color temp. via Tunable White: 2500...4000 K, 2700...5700 K CRI90
- CRI 90 versions available
- Stable light flux over length: active constant current regulators (ICs), PWM safe
- Embedded automatic quick protection against accidental miswiring up to 25 V
- Fully PWM dimmable from zero up to 2.5 kHz, audible noise free, suitable for quite places
- IP67 & IP66
- Salt-mist atmosphere resistant (acc. to IEC 60068-2-52, highest severity)
- UV radiation resistant (acc. to ISO 4892-2) / Mixed flowing gas corrosion resistant (IEC 60068-2-60)
- Designed, engineered and manufactured and tested in Italy (ISO9001, ISO 17025, ACCREDIA, VDE)

Преимущества продукта

- Color uniformity better than 3 SDCM on the entire LED strip and between strips
- LED lifetime acc.to IES LM-80 and IES TM-21 standards, and also internal OSRAM LAB tests
- Excellent robustness: single reel manufacturing technology (no solder joints on strip)
- Простой монтаж на различных гладких поверхностях с помощью клейкой ленты с обратной стороны
- Необычный дизайн и высококачественные материалы



Техническое описание продукта

Technical data


Электрические параметры

Номинальное напряжение	24,0 В
Тип тока	Постоянный ток
Номинальная мощность в ваттах на метр	30.9 Вт
Мощность	92,80 Вт
Диапазон входных напряжений тока	23...25 В
Accidental reverse input voltage protection up to	25 В

Фотометрические данные

Цветность светодиода	Dynamic White
Цветовая температура	2500...4000 К
Индекс цветопередачи Ra	80
Световой поток на метр	3356 лм
Световая отдача	108 лм/Вт
Стандартное отклонение эллипса соотв.	≤3 sdcм
Цветность света (обозначение)	2500...4000 К
Цветовая температура	3100 К

Размеры и вес



Длина	3000,0 mm
Длина кабеля	500,0
Вес продукта	173,00 g
Сечения кабеля, сторона ввода	0,5 mm ²
Ширина	11,1 mm
Высота	4,50 mm

Температуры и условия управления

Техническое описание продукта

Диапазон температур в процессе работы	-30...80 °C ¹⁾
t хранения	-40...85 °C

¹⁾ Exceeding the maximum ratings will reduce expected life time or destroy the LED strip.

Дополнительные данные

ID of contained light source [AGGR]	LS_TRV_286107
-------------------------------------	---------------

Сертификаты и Стандарты

Стандарты	CE/UL/ENEC/EAC
Energy efficiency class of the contained light source	F

Условия поставки

Код заказа	85395100000
------------	-------------

Environmental information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
Date of Declaration	18-04-2022
Primary Article Identifier	4062172196604
Declaration No. in SCIP database	In work

Загрузка данных

Файл	
	User instruction LINEARlight FLEX Protect Tunable White
	Product Datasheet LINEARlight Flex Protect Tunable White CRI90 specification sheet (EN)
	Brochures Light is freedom of design (EN)
	Certificates VDE ENEC CERTIFICATE 40052516 160823
	Certificates LF(P) TW G5 CB 180121
	Declarations of conformity Flex Protect TW G2 CE 4264939 180823
	Eulumdat LFP3400TW-G5-825.940-03 L1 LTD 130421
	IES data LFP3400TW-G5-825.940-03 L1 IES 130421

Техническое описание продукта

Ecodesign regulation information:

- This product is considered to be a "containing product" in the sense of Regulations (EU) 2019/2020 and (EU) 2019/2015.
- Tolerances of the reported values, are according to LED Modules Performance standard IEC/EN 62717.
- In general, the replacement of the contained light sources without permanent damage to the product with the use of common available tools is possible in the final application when they can be dismantled from the installation environment and substituted for the necessary number of light sources restoring its full electrical/mechanical/thermal/optical functionality by means of a professional installer. In the contrary, and limited to the LINEARlight Flex Diffuse, LINEARlight Rigid Finesse, GINO LED Flex Diffuse and LUMINENT Milky product families, the contained light source is an integrated part of the containing product and its removal can only be done by causing a permanent damage to the containing product due to its tight mechanical, electrical, optical, thermal interaction and/or environmental protection with or from the containing product. Therefore, a replacement of the light source with the use of common available tools is not justified.
- Dismantling of light sources from containing products at end of life: Containing products with light sources which are scalable in length can be cut to the length of the contained light source and if applicable mechanically detached from protective and/or optical covers. Containing products shall be separated from building material and/or from other additional mounting accessories by means of a professional installer. Separate control gear and light sources must be disposed of at certified disposal companies in accordance with Directive 2012/19/EU (WEEE) in the EU and with Waste Electrical and Electronic Equipment (WEEE) Regulations 2013 in the UK. For this purpose, collection points for recycling centres and take-back systems (CRSO) are available from retailers or private disposal companies, which accept separate control gear and light sources free of charge. In this way, raw materials are conserved and materials are recycled.

Данные для заказа

Product code	Описание продукта	Упаковка (цена/шт.)	Размеры (длина x ширина x высота)	Объем	Вес брутто
4062172196604	LFP3400TW-G5 - 825.940-03 L1	Shipping carton box 8	365 mm x 286 mm x 366 mm	38.21 дм³	5602.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Дополнительные аксессуары

Описание продукта	Название аксессуара	Код аксессуара
LFP3400TW-G5 -825.940-03 L1	ENDCAP -IP67 KIT 10PCS	▶ 4062172176552
LFP3400TW-G5 -825.940-03 L1	LTS-SLIMTRACK -2000 KIT 5 PCS	▶ 4062172207300
LFP3400TW-G5 -825.940-03 L1	FX-QMS-G1 -TU15H6-300	▶ 4052899448865
LFP3400TW-G5 -825.940-03 L1	FX-QMS-G1 -TU15H6W3-300	▶ 4052899448889
LFP3400TW-G5 -825.940-03 L1	FX-QMS-G1 -TU16H12W3-300	▶ 4052899448988
LFP3400TW-G5 -825.940-03 L1	FX-QMS-G1 -TU16H12-300	▶ 4052899448964
LFP3400TW-G5 -825.940-03 L1	FX-QMS-G1 -TU16H12LS-300	▶ 4052899449046

Техническое описание продукта

Примечание

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.