


BoxLED M CP G5

Светодиодные модули для светящихся рекламных надписей и фоновой подсветки



Характеристики продукта

- Цепь из 32 линейных светодиодных модулей
- Подсоединение с помощью гибких кабелей
- Maximum length of one chain: 9.80 m
- Степень защиты (модули): IP66
- Полностью интегрированный теплоотвод

Преимущества продукта

- Модули подходят для работы с монтажным профилем BackLED
- Равномерное освещение благодаря оптимизированным эллиптическим линзам
- Различные возможности для быстрого и простого монтажа: крепление с помощью болтов или защелок
- Высокий КПД модуля
- Однородный белый свет (стандартное отклонение согласования цвета, SDCM: 3)
- Очень большой срок службы
- Гарантия – 5 лет

Данные о продуктовой линейке

Оборудование/аксессуары

- Several types of OPTOTRONIC and ELEMENT 12 V power supplier
 - BoxLED mounting profile BX-MP-M-CP-G5-2M
 - BoxLED cable clip BX-CLIP-M-G5
-

Рекомендации по применению

Для получения дополнительной информации и изображения продукции, пожалуйста, ознакомьтесь с инструкцией.

Продажи и техническая поддержка

Продажи и техническая поддержка www.osram.com

Ecodesign regulation information:

- This product is considered to be a "containing product" in the sense of Regulations (EU) 2019/2020 and (EU) 2019/2015.
 - Tolerances of the reported values, are according to LED Modules Performance standard IEC/EN 62717.
 - In general, the replacement of the contained light sources without permanent damage to the product with the use of common available tools is possible in the final application when they can be dismantled from the installation environment and substituted for the necessary number of light sources restoring its full electrical/mechanical/thermal/optical functionality by means of a professional installer. In the contrary, and limited to the LINEARlight Flex Diffuse, LINEARlight Rigid Finesse, GINO LED Flex Diffuse and LUMINENT Milky product families, the contained light source is an integrated part of the containing product and its removal can only be done by causing a permanent damage to the containing product due to its tight mechanical, electrical, optical, thermal interaction and/or environmental protection with or from the containing product. Therefore, a replacement of the light source with the use of common available tools is not justified.
 - Dismantling of light sources from containing products at end of life: Containing products with light sources which are scalable in length can be cut to the length of the contained light source and if applicable mechanically detached from protective and/or optical covers. Containing products shall be separated from building material and/or from other additional mounting accessories by means of a professional installer. Separate control gear and light sources must be disposed of at certified disposal companies in accordance with Directive 2012/19/EU (WEEE) in the EU and with Waste Electrical and Electronic Equipment (WEEE) Regulations 2013 in the UK. For this purpose, collection points for recycling centres and take-back systems (CRSO) are available from retailers or private disposal companies, which accept separate control gear and light sources free of charge. In this way, raw materials are conserved and materials are recycled.
-

Примечание

В заказ могут быть внесены изменения без предварительного уведомления. Проверьте информацию на наличие ошибок. Убедитесь, что информация актуальна.